

New Product Bulletin



PART NUMBERS	3 BOLT MOUNT		POLE MOUNT		MAGNETIC MOUNT		FLEXI POLE MOUNT	
	281R-A	Amber	281RP-A	Amber	281RM-A	Amber	281RFP-A	Amber
	281R-B	Blue	281RP-B	Blue	281RM-B	Blue	281RFP-B	Blue
	281R-G	Green	281RP-G	Green	281RM-G	Green	281RFP-G	Green
	281R-R	Red	281RP-R	Red	281RM-R	Red	281RFP-R	Red
SINGLE BOLT MOUNT		281S	Red	Adaptor plate fitted to 3 bolt unit				

COOLDRIVE ARE PLEASED TO ANNOUNCE THE INTRODUCTION OF THE NEW 281 SERIES LED WARNING BEACONS FROM STAR!

The 281 Series Beacons are a complete family of LED Beacons that come with all the mounting types, various colour options, have a combined Strobe & Rotating functionality.

With ultra-high intensity LED's and 14 x customer selectable flash patterns that are 12 x strobe patterns and 2 x rotating patterns. There is also a steady burn option.

Multiple Beacons can be connected together via the S-Link System wire which provides synchronised flashing with all beacons connected or alternate flashing if required. Up to 6 beacons in total can be connected via the S-Link system.

LED STROBE / ROTATING BEACON

VOLTAGE:	9 - 32 Volt
CURRENT DRAW:	0.5amps at 12 volt & 0.25amps at 24 volt
PATTERNS:	12 x strobe patterns, 2 x rotating patterns, 1 x steady on
LENS COLOUR:	Amber, blue, green and red
LED COLOUR:	Warm white
LED'S:	12 x 1 watt star x-fire high intensity LED's, 50,000 hours LED lifespan
LENS:	Durable amber optical PMMA polycarbonate lens
HOUSING:	Lightweight black polycarbonate housing
MOUNTING:	5 DIFFERENT MOUNTING OPTIONS: <ul style="list-style-type: none"> • 3 bolt mount, slotted mounting holes to accommodate SAE & DIN mount • Magnetic mounts with rubber suction pad, 3.5m long spiral cable and cigarette accessory plug that has an on/off rocker switch and pattern select switch • DIN pole mount base • DIN flexi pole mount base • Single bolt mount - Adaptor plate kit fitted to 3 Bolt units
CIRCUITRY:	Conformal coated circuitry, fully sealed against dust and moisture
WIRING:	4 x wire; battery positive, earth, sync, pattern select, 250mm long lead
DIMENSIONS:	146mm width x 155mm height
APPROVALS:	SAE J845 Class I & CA13 Approval with ECE Reg R65 & R10
RATING:	IP67 rating
ORIGIN:	Manufactured in the USA
WARRANTY:	5 year warranty

