



# CABLE GLAND RANGE

## CONDUIT IP68



PART #	DESCRIPTION						QTY
<b>CG1025-10</b>	NC08	6.4mmID	10mmOD	12mm Thread	8.5mm Thread Depth		<b>10</b>
<b>CG1028-10</b>	NC08	6.4mmID	10mmOD	16mm Thread	10mm Thread Depth		<b>10</b>
<b>CG1030-10</b>	NC12	9.9mmID	13mmOD	16mm Thread	10mm Thread Depth		<b>10</b>
<b>CG1033-10</b>	NC16	12.8mmID	15.9mmOD	16mm Thread	10mm Thread Depth		<b>10</b>
<b>CG1035-10</b>	NC16	12.8mmID	15.9mmOD	20mm Thread	12.5mm Thread Depth		<b>10</b>
<b>CG1040-10</b>	NC20	16.6mmID	21.2mmOD	16mm Thread	12.5mm Thread Depth		<b>10</b>
<b>CG1042-10</b>	NC20	16.6mmID	21.2mmOD	20mm Thread	13mm Thread Depth		<b>10</b>
<b>CG1045-10</b>	NC20	16.6mmID	21.2mmOD	25mm Thread	13mm Thread Depth		<b>10</b>
<b>CG1048-2</b>	NC25	21.2mmID	25.3mmOD	25mm Thread	13mm Thread Depth		<b>2</b>
<b>CG1049-2</b>	NC32	29mmID	33mmOD	32mm Thread	14mm Thread Depth		<b>2</b>

## QUICK CONNECT



PART #	DESCRIPTION						QTY
<b>CG1050-10</b>	NC08	6.4mmID	10mmOD	12mm Thread	10mm Thread Depth		<b>10</b>
<b>CG1053-10</b>	NC12	9.9mmID	13mmOD	12mm Thread	12mm Thread Depth		<b>10</b>
<b>CG1055-10</b>	NC12	9.9mmID	13mmOD	16mm Thread	10mm Thread Depth		<b>10</b>
<b>CG1058-10</b>	NC16	12.8mmID	15.9mmOD	16mm Thread	12.5mm Thread Depth		<b>10</b>
<b>CG1060-10</b>	NC16	12.8mmID	15.9mmOD	20mm Thread	12.5mm Thread Depth		<b>10</b>
<b>CG1063-10</b>	NC20	16.6mmID	21.2mmOD	20mm Thread	13mm Thread Depth		<b>10</b>
<b>CG1064-10</b>	NC25	16.6mmID	21.2mmOD	25mm Thread	13mm Thread Depth		<b>10</b>
<b>CG1066-2</b>	NC25	21.2mmID	25.3mmOD	25mm Thread	13mm Thread Depth		<b>2</b>
<b>CG1068-2</b>	NC32	29mmID	33mmOD	32mm Thread	14mm Thread Depth		<b>2</b>

## 90° QUICK CONNECT



PART #	DESCRIPTION						QTY
<b>CG1003-10</b>	NC08	6.4mmID	10mmOD	12mm Thread	8.5mm Thread Depth		<b>10</b>
<b>CG1005-10</b>	NC12	9.9mmID	13mmOD	16mm Thread	10mm Thread Depth		<b>10</b>
<b>CG1007-10</b>	NC16	12.8mmID	15.9mmOD	16mm Thread	10mm Thread Depth		<b>10</b>
<b>CG1010-10</b>	NC16	12.8mmID	15.9mmOD	20mm Thread	12.5mm Thread Depth		<b>10</b>
<b>CG1012-10</b>	NC20	16.6mmID	21.2mmOD	20mm Thread	13mm Thread Depth		<b>10</b>
<b>CG1015-10</b>	NC20	16.6mmID	21.2mmOD	25mm Thread	13mm Thread Depth		<b>10</b>
<b>CG1017-2</b>	NC25	21.2mmID	25.3mmOD	25mm Thread	13mm Thread Depth		<b>2</b>
<b>CG1020-2</b>	NC32	29mmID	33mmOD	32mm Thread	14mm Thread Depth		<b>2</b>

## CABLE GLAND - KEY FEATURES

- UL Approved Nylon PA66 Material
- Resistant to Oils, Greases, Solvents, Fuels
- Operating Temperature: Continuous Range -40°C to +100°C (Peak +120°C)
- RoHS Compliant
- UL94V-2 Flammability Rating
- Non Slit Tubing

## CONDUIT FASTENERS

Corrugated Tube



PART #	DESCRIPTION		QTY
<b>CG1070-10</b>	NC08	H:21mm W:20mm	<b>10</b>
<b>CG1072-10</b>	NC12	H:23.7mm W:22.7mm	<b>10</b>
<b>CG1074-10</b>	NC16	H:26.34m W:25.5mm	<b>10</b>
<b>CG1076-10</b>	NC20	H:31.5mm W:31.3mm	<b>10</b>
<b>CG1077-10</b>	NC25	H:35mm W:36.5mm	<b>10</b>
<b>CG1079-10</b>	NC32	H:46.26mm W:47.2mm	<b>10</b>