

NEW PRODUCT BULLETIN 37 2014

CoolDrive is pleased to announce the introduction of the new

Jaylec Digital Multimeters.

T02224, T02225, T02226.

T02224

AC/DC Digital Multimeter

2000 Digital Display Counts

- · Auto ranging · CAT III 600V
- 9 Functions DCV, ACV, DCA, ACA, Resistance, Diode Check, Continuity,

Diode Check, Continuity, Dwell Test 4-8Cyl, Tach Test 4-8 Cyl

- Min / Max
- Backlight Data Hold
- Low Battery Indicator
 Includes Test Leads
- Includes Test Leads and User Manual
 - Power Supply 2 x AAA batteries. (Batteries not included)



T02225

AC/DC Digital Multimeter

4000 Digital Display Counts

- Auto ranging
 CAT III 600V
- 14 Functions DCV, ACV, DCA, ACA, Resistance, Capacitance, Frequency, Temperature, HFE Transistor, NCV (Non Contact Voltage Detector), Diode Check, Continuity, Dwell Test 4-8Cyl, Tach Test 4-8Cyl • Min / Max
- · Backlight · Data Hold
- · Low Battery Indicator
- Includes Test Leads and User Manual
- Power Supply 1 x 9V battery. (Batteries not included)



T02226

AC/DC Digital Multimeter

6000/22000 Digital Display Counts

- · Auto ranging · CAT III 1000V · True RMS
- 12 Functions DCV, ACV, DCA, ACA, Resistance, Capacitance, Frequency, HFE Transistor, NCV (Non Contact Voltage Detector), Diode check, Continuity, Relative Measurement
 - Min / Max Backlight Data Hold Low Battery Indicator
 - Includes Test Leads and User Manual USB interface
 - Power Supply 4 x AA batteries.

(Batteries not included)





NEW PRODUCT BULLETIN 37 2014

CoolDrive is pleased to announce the introduction of the new

Jaylec Clamp Meter & Infared Thermometer.

T02227 & T02230

T02227

AC/DC Digital Clamp Meter

4000 Digital Display Counts

- Auto ranging CAT III 600V
- 10 Functions DCV, ACV, DCA, ACA, Resistance, Capacitance, Frequency, Temperature, Diode Check, Continuity
- Min / Max Backlight Data Hold Low Battery Indicator
- · Includes Test Leads and User Manual
- Power Supply 1 x 9V battery. (Batteries not included)





T02230

Non-Contact Infrared Thermometer

Precise Non-Contact

- Temperature Range -20°C 537°C
- · Laser Target Pointer
- OC / OF Selection
- · Reading Hold
- · Max, Min, Ave, Diff
- · Low Battery Indicator
- Power Supply 1 x 9V battery.
 (Batteries not included)