

# STM

LEADERS IN FLUID TRANSFER SOLUTIONS

## CK602

### 1:1 205L AIR OPERATED OIL PUMP

- Flow rate up to 18 LPM (free flow)
- Fast & efficient method for dispensing directly from 205L drums
- Comes complete with air regulator, gauge, on/off air valve & lubricator



## DM60205

### 60L & 205L DRUM LEVEL GAUGE

- Reusable meter to provide an accurate remaining oil level in 60 & 205L drums.
- Robust design to provide long service life.
- Large, easy to read gauge in litres.
- Fits into the secondary port on the oil drum.
- Suitable for most common fluids, including engine oil, hydraulic oil, gear oil, ATF, coolant & waste fluid.
- Helps remove the risk of problematic stock outs.



## CA465G2

### 20L GEAR OIL PUMP

- Easy downstroke action
- Approximately 14 strokes per litre
- Suitable for gear oil, engine oil & hydraulic oil
- 1.5 metre anti-kink hose
- Fitted with anti-drip nozzle & drain back nozzle holder
- Nylon head & handle
- Special threaded adaptor designed & engineered to suit most plastic & metal drums
- Compatible for most kinds of drum with Rieke adaptor



## CA465ATF2

### 20L ATF OIL PUMP

- Easy downstroke displacement
- Approximately 14 strokes per litre
- 1.5 metre anti-kink hose
- Fitted with anti-drip nozzle & drain back nozzle holder
- Ground shaft with 'O' ring seal
- Nylon head & handle
- Special threaded adaptor designed & engineered to suit most plastic & tin plate drums
- Telescopic extension
- Replaceable stainless steel mesh filter (100 x 41 SWG) which prevents contamination of system



## DITIAOD3065E

### OIL DRAINER - 65L CAPACITY

## DITIAOD3090E

### OIL DRAINER - 90L CAPACITY

- Suitable to drain waste oil by gravity from engines, gear boxes & differentials of all vehicles
- 18L waste collection bowl & 606mm diameter extension funnel
- 2-meter discharge hose



## CA586

### 1L TOM THUMB OIL PUMP

- 1 litre top up utility pump with integrated carry handle
- Ideal for hard to get to oiling points
- 500 mm long PVC hose & spout
- Aluminium construction
- Nylon head and handle
- Nozzle drain back holder
- 10 ml per stroke
- Suitable for oils, ATF and brake fluid
- Typically used for outboard and two stroke motors, chain saws, motor vehicles & odd jobs around the home



## CA469G

### 60L SPRING OPERATED OIL PUMP

- Approximately 2 strokes per litre
- Unique spring actuated displacement
- 1.5 metre anti-kink hose
- Fitted with lever operated trigger nozzle and drain back nozzle holder
- Ground shaft with "O" ring seal
- 2" bung thread



## CA469ATF

### 60L SPRING OPERATED ATF PUMP

- Approximately 2 strokes per litre
- Unique spring actuated displacement
- 1.5 metre anti-kink hose
- Lever operated trigger nozzle and drain back nozzle holder
- Die cast head
- Ground shaft with "O" ring seal
- 2" bung thread

## CA972

### 60L DRUM TROLLEY

- 60 litre trolley
- Solid steel construction
- Lightweight & easy to use
- 2 year guarantee

